Data sheet

Update: 20180419

AFH-120-003

Advantages:

- Small size, Max. output achieve 124dB.
- Can be used in CIC.

Mechanical data:

- Dimensions:



- Port location: 12C
- Solder type: SAC305, and ROHS compliance

Electrical properties:

- Isolation: The case will be electrically isolated from internal coil
- DCR and impedance:

Item	specification
DC resistance	120Ω±10%
Imp@500 Hz	165Ω±15%
Imp@1 kHz	248Ω±15%

Data sheet

Update: 20180419

AFH-120-003

Acoustic specification:

1, Test condition

1.1 Driver: CV 346mVrms

1.2 Tube and cavity: 10mm*dia1.0mm tube into 2CC coupler

1.3 Source requirements: source impedance <1ohm.

2, Typical response curve and specification:



Specification	Frequency(Hz)	Minimum	Nominal	Maximum
Sensitivity	200	103	106	109
Sensitivity	500	101	104	107
Sensitivity	1000	99	102	105
Peak 1	2500-3100	106	109	112
Peak 2	5200-6200	114	116	118

3, Distortion specification:

Frequency(Hz)	Drive (Vrms)	Limit (%)
1/3 Peak 1	0.346	5%
1/2 Peak 1	0.346	5%

Data sheet

Update: 20180419

AFH-120-003

Port location explanation:

- Example 12S, 12 indicates the port location,S indicates tube on the centerline, details refer to below:



Port detail code:

N – no tube
B – tube away from the cover
C – tube near the cover
S – tube on the centerline
T – port on Top surface
O – other situation, check the drawing

Storage and operating requirements:

- Follow below table:

Item	Temperature (ºC)	Humidity (%RH)	barometric pressure (hPa)
Storage	-40 ~ 63	10 ~ 60	500 ~ 1060
Operating/test	15 ~ 30	45 ~ 85	860 ~ 1060
Judgment	18 ~ 22	60 ~ 70	860 ~ 1060

Website: www.china-armature.com
Office Tel: (+86) 0519-81882133
Mail box: sales@china-armature.com
Address: No.7 Lanxiang Road economic development zone
Wujin district Changzhou City China